




XL400/410e - Tag and Label Printer



Easy Connectivity



Intelligent
Printhead



High-Tech Movable
Sensor



The Standard for Reliable
Barcode Printing

XL400e/XL410e - General Specifications

MODEL		XL400e	XL410e
PRINTING SPECIFICATION			
Print Method		Direct Thermal, Thermal Transfer	
Print Resolution		203 dpi (8 dpmm)	305 dpi (12 dpmm)
Print Speed		Up to 8 ips	Up to 6 ips
Max. Print Area	Width	3.94" (100 mm)	3.94" (100 mm)
	Length	11.8" (300 mm)	9.4" (240 mm)
MEDIA SPECIFICATION			
Sensor Type		<ul style="list-style-type: none"> • Reflective sensor for use with pre-printed marks • Adjustable See-through sensor for die-cut media; center-hole, side-hole and side-notch tag 	
Media Type		Label, Tag, Fan-fold	
Media Size	Labels	Min. 1.26" (32 mm) W x 0.75" (19 mm) L Max. 4.13" (105 mm) W x 9.45" (240 mm) L	
	Tags	Min. 1.26" (32 mm) W x 0.98" (25 mm) L Max. 4.13" (105 mm) W x 9.45" (240 mm) L	
	Thickness	Max. 12 pt. (0.3 mm)	
	Outer Diameter	9.84" (250 mm)	
	Core Size	4" (optional 3" core)	
Ribbon		Max 4.01" (102 mm) x 1473' (450 m), CSI	
FONTS / SYMBOLOGIES			
Font	Internal	Bitmap Font: XU, XS, XM, XB, XL, OCR-A, OCR-B; Outline Font: CGTimes, CGTriumvirate	
	Downloadable	TrueType Font	
Barcode Symbolologies	Linear	UPC-A/E, EAN, CODE39, CODE93, CODE128, UCC/EAN128, Interleaved 2 of 5, Matrix 2 of 5, NW-7, MSI, Bookland, POSTNET	
	2-Dimensional	QR Code, PDF417, Veri Code, Maxi Code, Data Matrix	
INTERFACE SPECIFICATIONS			
Processor		32-bit RISC	
Interface	Standard	RS232C	
	Options	Parallel: IEEE 1284, Centronics; 10/100BaseT, IEEE 802.11; USB	
OPERATING CHARACTERISTICS			
Power Requirements		AC110/220 V (±10%), 50/60 Hz (±1%)	
Environment	Operating	41 - 104°F (5 - 40°C), 30 - 80% RH, non-condensing	
	Storage	23 - 140°F (-5 - 60°C), 30 - 90% RH, non-condensing	
Regulatory Approvals		CE, TÜV-GS, UL, CSA, FCC Class A, CCC	
Dimensions		19.6" W x 11.8" D x 11.5" H (302 mm W x 552 mm D x 294 mm H) 30.8 lbs. (14.0 kg)	
OPTIONAL ACCESSORIES			
Stacker, Memory Expansion, Real-Time Calendar/Clock			
OPERATIONAL FEATURES			
Function	Firmware Features	Batch Separator (Mark or Cut), Intelligent Printhead Control Regulating Print Temperature, Status Report, Graphics, Sequential Numbering, Form Overlay Store, Customized Design Character, Reverse Image, Line Print, Hex Dump Print, Format Store, Zero Slash Switchover	
	Self Diagnosis Tools	Head Check, Paper End Detection, Ribbon-End / Near-End Detection, Head Open Detection, Memory Card Error Detection, Test Print, Open Cutter-Cover Detection	

*Specifications subject to change without notice

SATO America, Inc.

10350-A Nations Ford Road, Charlotte, NC 28273
Phone: (704) 644-1650 Fax: (704) 644-1662
E-mail: satosales@satoamerica.com

© 2005 SATO America, Inc. All rights reserved. Rev. 05/05