

# CT 400

## Large Impact in a Compact Design

The SATO CT 400 is the understated professional. Top-speed throughput is housed in a robust, easy-to-maintain unit with a choice of interfaces for almost all systems. The CT 400 combines a modern, compact design with powerful state-of-the-art RISC technology, ideal for a wide range of applications.


- ✓ *High Speed Throughput*
- ✓ *200/300dpi*
- ✓ *4 inch print width*
- ✓ *Choice of Interfaces*
- ✓ *Compact*
- ✓ *Linerless Option*

**High-Speed** - At the heart of the CT 400 printer is the new generation, ultra high-speed processor. The CT printers process data virtually instantaneously and print continuously, even when the data and graphics vary on every label.


**Compact** - featuring a small footprint and weighing merely 3kg, the SATO CT printers deliver a high performance, even where workspace is restricted.

**Flexible** - Compatible with Windows®, labels can be printed from any Windows® based application. The range of interfaces, also allows the CT to be connected to almost any PC or terminal.

**Effortless** - Designed with the user in mind, the CT printers are quick to install, easy-to-use and easy-to-maintain.



# Compact Series



**CT 400**

**CT 410**

<b>Printing Method</b>	Direct Thermal/Thermal Transfer or Direct Thermal only	
<b>Print Resolution</b>	8 dots/mm (203 dpi)	12 dots/mm (305 dpi)
<b>Print Speed</b>	Up to 150 mm/second (6 ips)	Up to 100 mm/second (4 ips)
<b>Max. Print Width</b>	104 mm (4.1")	
<b>Max. Print Length</b>	400 mm (15.7")	
<b>Media Size</b>	Min. 25 mm (1") W x 15 mm (0.6") L Max. 118 mm (4.6") W x 400 mm (15.7") L	
<b>Ribbon Size</b>	Standard Widths: 44 mm (1.75"), 76 mm (3"), 110 mm (4.33")	
<b>Dimensions</b>	198 mm W x 230 mm D x 181 mm H (7.8" W x 9.1" D x 7.1" H)	
<b>Weight</b>	3 kg (6.6 lbs)	

**Memory:**

8 MB SRAM  
2 MB Flash ROM

**Processor:**

32-BIT RISC

**Media:**

Roll or fan-fold die cut labels, plain paper face stock and synthetics. Continuous stock using software control. Centre justified.  
Max. Caliper: 0.19 mm (0.0075")  
Max. Roll Diameter: 110 mm (4.4")  
Wind: Face-Out

**Ribbon:**

Max. Roll Diameter: 39 mm (1.5")  
Min. Core Diameter: 12.7 mm (0.5")  
Wind: Face-Out

**Sensing:**

Transmissive sensor for die cut labels and tags. Reflective sensor for use with pre-printed sensing marks. Automatic or programmable setting of top of form.

**Printer Control:**

User programmable via data stream  
Windows Printer Driver (provided)

**Interface:**

Parallel I/F (std.):  
• ECP Parallel IEEE1284  
Optional I/F  
• Serial RS232C highspeed  
• USB  
• LAN

**Barcode Symbolologies:**

Linear: UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/EAN 128  
2-Dimensional: PDF417, Micro PDF417, Truncated PDF417, Maxicode, Data Matrix, QR Code, RSS-14

**Barcode Ratio:**

2:1, 3:1, 5:2 or individually adjustable bar widths

**Barcode Height:**

Programmable, 4 to 600 dots

**Human Readable Fonts:**

12 proportional, mono-spaced and outline fonts (Code page 858, others available)  
Internal CG Triumvirate® and CG Times® fonts plus downloaded TrueType® fonts, scalable from 8 to 72 points

**Flexibility:**

360° rotation of barcodes and text, character expansion horizontally and vertically, form overlay for high-speed editing of complex formats.

**Graphic Support:**

SATO Hex/binary format  
PCX format  
BMP format

**AC Power:**

115V (± 10%), 14.5VDC (± 5V),

**Environmental:**

Operating: 5° to 40°C (41° to 104°F)  
15-85% RH, non-condensing  
Storage: -5° to 60°C (23° to 140°F)  
max. 90% RH, non-condensing  
ESD: 8kV

**Approvals:**

CE, UL, CSA, TÜV

**Options:**

Label Cutter (factory installed), Label Dispenser (factory installed), 220 V Power Supply, Smart Keyboard, Offwinder, Rewinder

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • Germany • OPAL Associates GmbH • Lohnerhofstrasse 2 • D-78467 Konstanz Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalqmbh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 Jülich • Telefon +49 (0)2461 936 770 • Telefax +49(0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • Austria • OPAL Associates GesmbH • Voralberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5223 58833 • Telefax +43 (0)5223 521569 • Email info@opal-holding.com • URL <http://www.opalqmbh.at/>

