

NLS-MT90

Model: MT9051-2WF

Portable Data Collector



























Features

■ Superior Barcode Reading Performance

Armed with Newland's sixth-generation of **WIMG®** technology and its state-of-the-art 2D mega-pixel engine, the new NLS-MT90 can decode even poorer quality barcodes, such as soiled or wrinkled labels, with ease.

User-focused Ergonomics

The user-focused ergonomic design of the NLS-MT90 renders a lightweight and well-balanced device that reduces stress and fatigue during extended work sessions. Its ergonomically positioned side scan buttons provide the most comfort to use for either rightor left-handed operators.

■ Diverse Functionalities

Beyond the flexibility of its dual SIM card system, the NLS-MT90 offers Bluetooth/ dual band WiFi 2.4GHz and 5GHz / 4G/3G/GPS/GPRS/Camera/ NFC functionalities to meet various application needs.

Application Scenarios

■ Long-lasting Battery Life

The NLS-MT90 is equipped with a 4500mAh battery that provides a full-shift battery life of up to 10 hours from a single charge.

Heavily Customized Android

The value-added features of the NLS-MT90, including application protection and admin tool, seek to shore up Android's data security.

Industrial-grade Durability

The NLS-MT90's rugged housing is sealed to IP65 standards for protection against dust and water and withstands 1.5m drops to concrete.

Current models released

MT9051-2WE (2D mega-pixel imager)



NLS-MT90

Portable Data Collector

SCANNING MADE SIMPLE

Performance	Processor	1.3GHz quad-core 64-bit processor
	Operating System	Android 7.0 (64-bit)
	Memory	2GB RAM, 16GB ROM
	Interface	Micro USB 2.0 OTG, Battery charging over USB supported
Physical	Dimensions	Maximum Size: 155(L) × 78.5(W) × 20.5(H)mm; Handheld Size: 155(L) × 76(W) × 18(H)mm
	Weight	265g (including battery)
	Display	5" (1280×720) capacitive touch screen
	Keypad	10 keys (side keys included)
	Notification	Vibrator, speaker and multi-color LEDs
	Battery	3.8V, 4500mAh
	Expected Battery Life	10 hours
	Expected Charge Time	<5 hours (charge via AC adapter)
	Camera	8 megapixels, auto focus, with LED flashlight
	GPS	GPS (AGPS), GLONASS
	Expansion	Micro SD card (max. 32GB) slot
	AC Adapter	Output: DC5V, 2.0A Input: AC100~240V, 50~60Hz
Environmental	Operating Temperature	-20°C to 55°C (-4°F to 131°F)
	Storage Temperature	-30°C to 70°C (-22°F to 158°F)
	Humidity	5% to 95% (non-condensing)
	Static Discharge	±15 kV (air discharge), ±8 kV (direct discharge)
	Drop	1.5m drops to concrete, 1.8m drops to concrete with rubber boot
	Sealing	IP65
Barcode	Laser aiming	1D: EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Code 39, Codabar, UCC/EAN128, RSS, ITF,
Scanning	Mega-pixel	ITF14, ITF6, ISSN, ISBN, Standard 25, Matrix 25, Industrial 25, Plessey, MSI Plessey, Code
		11, Code 93, etc.
		2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec,
		Chinese Sensible Code, Maxicode, Composite, etc.
RFID	13.56MHz RFID	ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693
Wireless	WLAN RADIO	IEEE 802.11 a/b/g/n, 2.4GHz and 5GHz
	WWAN RADIO	2G: GSM/GPRS/EDGE (850/900/1800/1900MHz)
		3G: WCDMA (B1, B2, B5, B8)
		TD-SCDMA (B34, B39)
		CDMA2000 1X/ EV-DO Rev. A (BC0)
		4G: TD-LTE (B38, B39, B40, B41)
	-	FDD-LTE (B1, B3, B7, B8, B20)
	WPAN RADIO	Bluetooth 4.0 LE
Optional Accessories		Charging cradle, pistol grip, rubber boot, battery, AC adapter, cable, wrist lanyard, hand strap.
pecifications are subject t	to change without notice.	Version: V1.

Newland China

